

SUBMITTAL DATA – VRF INDOOR UNIT CTVS-ICC-X-010-A-CE-DC-1 8 Way Compact Cassette DC

| Job: | Engineer: |
|---------------------|---|
| Location: | Architect: |
| Schedule No.: | Date: |
| System Designation: | For: □Reference □Approval □Review □Construction |

FEATURES

- All DC Inverter Technology
- 7 Speed
- High-lift Drain Pump
- Wide Application Range
- Single Fan Motor

- Flexible Control and Easy Maintenance
- Heating and Cooling
- Convenient Installation

| SPECIFICATIONS | | |
|-------------------------------------|------------|-------------------|
| PERFORMANCE | | |
| Nominal Cooling Capacity | Btu/h | 9,600 |
| | Kw | 2.8 |
| Nominal Heating Capacity | Btu/h | 10,900 |
| | Kw | 3.2 |
| ELECTRICAL DATA | | |
| Power Supply | V/Ph/Hz | 220-240/1/50-60 |
| Power Input (10 Pa) Cooling | Kw | 35 |
| Power Input (10 Pa) Heating | Kw | 35 |
| Min. Voltage | Volts | 198 |
| Max. Voltage | Volts | 264 |
| MCA | Amp | 0.43 |
| MFA | Amp | 15 |
| Rated Motor Output | Kw | 0.037 |
| FLA | Amp | 0.344 |
| GENERAL DATA | | |
| Airflow rate 3 | m3/h (CFM) | 414(244) |
| | m3/h (CFM) | 380 (224) |
| | m3/h (CFM) | 345 (203) |
| | m3/h (CFM) | 313 (184) |
| | m3/h (CFM) | 288 (169) |
| | m3/h (CFM) | 268 (158) |
| | m3/h (CFM) | 238 (140) |
| Sound pressure level 5 | dB(A) | 35 |
| | dB(A) | 34 |
| | dB(A) | 33 |
| | dB(A) | 29 |
| | dB(A) | 26 |
| | dB(A) | 23 |
| | dB(A) | 22 |
| Body Net/Gross weight | KG | 18/23.8 |
| | (Lbs) | (39.7/52.5) |
| Panel Net/Gross weight | KG (Lbs) | 2.5/4.5 (5.5/9.9) |
| Refrigerant type | | R410A |
| Design pressure (H/L) | Мра | 4.4 / 2.6 |
| Refrigerant Pipe Connections (inch) | Gas | 1/4" |
| . , | Liquid | 1/2" |
| Drain Pipe | inch | 1" |



Notes:

- 1.Indoor temperature 27°C DB, 19°C WB; outdoor temperature 35°C DB; equivalent refrigerant piping length 7.5m with zero level difference.
- 2.Indoor temperature 20°C DB; outdoor temperature 7°C DB, 6°C WB; equivalent refrigerant piping length 7.5m with zero level difference.
- 3. Air flow rate are from the highest speed to the lowest speed, total 7 rates for each model.
- 4. Sound pressure level is from highest level to lowest level, total 7 levels for each model. Sound pressure level is measured 1.4m below the unit in a semi-anechoic chamber.
- 5.Unit body dimensions given are the largest external dimensions of the unit, including hanger attachments.

OPTIONAL ACCESSORIES

Wireless Thermostat CTVS-C-WL05B (not included)



DIMENSIONAL DRAWINGS - INCHES (MM)

