

COMFORT TIME

Para un clima de tranquilidad total



serie 17
NEXT LEVEL


Elegant



SPLIT TYPE AIR CONDITIONER



serie 17
NEXT LEVEL


Elegant

PRODUCT SPECIFICATION SHEET				CTA-I12L3217	CTA-I18L3217	CTA-I24L3217
AUX Split Room Air Conditioner			No	CTA-O12L3217	CTA-O18L3217	CTA-O24L3217
				/	/	
			Model	12K-cool only luxury model	18K-cool only luxury model	24K-cool only luxury model
Nameplate Parameter	Rated Capacity	Cooling	BTU/H	12000	18000	24000
		Heating	W	/	/	/
		Dehumidifying	Kg/h	1.2	1.6	2.96
	Rated Power Consumption	Cooling	W	1320 (210-1600)	1750 (230-1900)	2.3(0.44-2.64)
		Heating	W	/	/	/
	Rated Running Current	Cooling	A	6.0(1.7-7.2)	8.5 (1.1-8.9)	10(2-12)
		Heating	A	/	/	/
	Electricheating power	Power	W	/	/	/
	Max. Input Power		W	1600	1900	2.8
	Max. Input Current		A	8	9.0	13
	EER Cooling		W/W	4.50	5.5	3.04
	COP Heating		W/W	/	/	/
	Power supply source		V/Ph/Hz	208~230V 60Hz	208-230V~/1/60Hz	208~230V 60Hz
	Refrigerant		/	R32	R32	R32
	Refrigerant Charged		g	400	630	0.75
	Max. Discharge Pressure		Mpa	4.3	4.3	4.3
	Max. Suction Pressure		Mpa	2.5	2.5	2.5
	Air Flow Volume		m3/h	600	950	1300
	Noise level		dB (A)	42	47	50
Noise level		dB (A)	52	52	57	
Indoor unit weight (Net)		Kg	8	11.5	13	
Outdoor unit weight (Net)		Kg	17	23	38	
IDU SIZE	Net Dimension	mm	761*295*200	960x315x222	1089x328x244	
	Packing Dimension	mm	825*367*277	1020x375x305	1155x397x312	
ODU SIZE	Net Dimension	mm	703*456*260	709x537x281	825x655x310	
	Packing Dimension	mm	760*510*305	825x345x595	945x725x435	
Container Loading 40HC		sets	350	210	156	



Todo el juego Mini Split viene con kits de instalación (cable y cobre-aluminio de 3 m) y control remoto.